

#Scanmar QBC-X1 Charger v01-21

# QBC-X1 Charger

- Configuration of power level and transmission frequency (FID)
- Choice of rapid or normal refresh rate (telegrams)



## Charging Technology

New charging and battery technology delivers rapid charging and the option to activate additional sensor functions.

## Compatibility

QBC-X1 is a configuration and test unit compatible with all Scanmar sensors, except the TrawlEye, and has several useful features

**Sensor Programmer and Charger****QBC-X1**TECHNICAL SPECIFICATIONS

---

**Mains**

Voltage: 90-264 VAC

Frequency: 47-63 Hz

Current: 2 A max

Power Consumption: 70W max

**Charging Voltage and Current**

HC4/MP4 Sensor: 36V at 0.5A

ScanSensor (SS4): 16V at 5A

**Sensors Supported**

All chargeable Scanmar sensors (except TrawlEye)

**Display**

Type: Monochrome

Resolution: 128x64

Size: 3"

**Keypad**

4 keys

**Environmental**

Tolerates exposure to water spray

Operating Temperature.: -10 to 40°C

Storage Temperature.: -20 to 55°C

**Compass Safe Distance**

To magnetic compass: 20cm

**Weight**

Approx. 2 kg

**Main dimensions**

Length: 142 mm

Width: 203 mm

Height: 64 mm

